

## **MT-4 series-TF-1280H**

### **FEATURES:**

- Sparates speed operation on locking installation easy and convenient to operate. Excellent & exact precision
- Opening model on precision heavy duty installation. Essy to save and repair.
- 12-speed gear box more function
- The locking device adopts the segmented operation, which is simple, convenient, easy to operate and accurate and accurate.
- The hydraulic device is open and easy to maintain and maintain.

### **Specification:**

ITEM Type				TF-1280H
Capacity	Drilling	Stell Steel		Ø50
		Castiron cast iron		Ø60
Maximum working energy	Tapping	Stell Steel		Ø30
		Castiron cast iron		Ø38
	Boring Boring	Stell Steel		Ø85
		Castiron cast iron		Ø120
Spindle stroke			H	250
Size of morse Taer spindle spindle				NO.4
Spindle speed				44-1500 (12)
Spindle Feeds Spindle feed range				(0.005 / 0.09 / 0.15)
Column Diameter			A	300 (11 7/8 ")
Max.distance, column sarace spindel center The maximum distance from the column to the center of the spindle			B	1250
Minimal distance to the center of the spindle			C	330
Horiontal Travel of Meadstock			D	920
Max.distance, base to spindel The maximum distance of the spindle			E	1210
Mindistance, base to spindel Spindle minimum distance			F	290
Overall height of column			G	2140
Machine height of column			I	2585
Dimensions of hase [L x H xK] Base size				1800 x800 x 170
Effective area of table [R x S x T] Workbench effective area				650 x 500 x 410
Spindle drive motor [HP] Spindle motor				3HP (4P x 8P)
Arm motor (HP) arm drive motor				2HP
Coolant pump [HP] cool caravan				1 / 8HP
Oil motor [HP] hydraulic motor				1HP
Inverter frequency converter				

Net weight -Approx [kg]	2050kgs
Gross weight-Approx [kg]	2150 kgs
Measurement [L x W x H] Packing size	2290 x 1100 x 2230

