

Bed type & CNC

PF-6SH-PLC

Feature :

- Spindle Motor Stop brake Auto Power off
- 5 HP Spindle Motor
- Touch Simple Automatic Control
- 254 x 1372 mm table standard
- 305 x 1372 mm table optional
- Spindle Taper NST# 40
- Special Square Head for Step Speed
- X-axis Dovetail slide way
- Y, Z-axes Square Way
- X, Y-axes Coated with Turcite-B
- X, Y, Z-axes Hardened & Ground
- Automatic Lubrication sideways and feed screws ensures, Accurate motion for all parts
Lubrication interval is 60 minutes optional

Optional Equipment:

- Coolant System
- Chip (pan) Guard
- Adjustable Safety Table Cover
- Work Lamp
- Milling Chuck with Collets
- Clamping Kits
- Machine Vise
- Percision Ball Screw for X, Y-axes
- Digital Readout for X, Y, Z-axes
- Electric Cabinet with 6 Drop Control Panel + spindle Motor Auto Brake
- Y-axes Power Feed

Standard Accessories:

- Horizontal Mill Arbor
27mm 1/pcs
- Horizontal Draw Bar 1/pcs
- Vertical Draw 1/pcs
- Tools & Tool Box
- One Shot Lubrication
- Front & Rear Plastic
Splash Guard
- Operation Manual