

CBM LARGE DIAMETER MODULAR ADJUSTMENT BORING HEAD WITH DIAMETER OVER 200MM

CBM Large Diameter Modular Adjustment Boring Head with Diameter over 200mm.



鑿頭型號 Boring Head Type	型號 Type	CBM200	CBM300	CBM400	CBM500	CBM600	CBM900	CBM1200	CBM1600
	正反鑿頭長度 LA (mm) Length	160	160	160	160	180	180	210	210
	整組重量 Total Weight (kg)	7.68	8.48	9.28	10.08	16.48	22.78	35.05	40.25
	正鑿加工直徑 ØDA(mm) Forward Boring Diameter	200-310	300-410	400-510	500-610	600-900	900-1200	1200-1600	1600-2000
	反鑿加工直徑 ØDB(mm) Reverse Boring Diameter	210-320	310-420	410-520	510-620	610-910	910-1210	1210-1610	1610-2010
	外鑿加工直徑 ØDC(mm) External Boring Diameter	190-310	290-410	390-510	490-610	590-910	890-1210	1190-1610	1590-2010
外鑿鑿頭長度 LC (mm) External Boring Length	220	220	220	220	240	240	270	270	
組合型式 Module	接合刀桿 Taper Shank	BT50-BST / NT50-BST 系列 BT50-BST / NT50-BST Series				BT50-FMA47.625			
	連接盤 Flange	BR200				BR600	BR900	BR1200	BR1600
		合金鋼 Alloy Steel				鋁合金 Alum. Alloy			
	橫向滑板 (鋁合金) Extension Slide(Alum. Alloy)	RST200	RST300	RST400	RST500	RST300x 2只(pieces)	RST400x 2只(pieces)	RST500 x 2只(pieces)	
	重量Weight(kg)	1.1	1.9	2.7	3.5	3.8	5.4	7	
	平衡滑塊/重量 Balance Base/Weight	RCM200 / 1.7 KG							
	微調滑塊/重量 Finish Head/Weight	CM200 / 1.95 KG							
刀片座 Insert Holder	正鑿 Forward Boring SP68 / 反鑿 Reverse Boring SA68 / 外鑿 External Boring ESP68								
適合刀片 Applicable Insert	CC09 / M4 / T15, TP09 / M2.5 / T8, TC11 / M2.5 / T8								